

KOLLEZI

○ ACE



WWW.KOLLEZI.COM

Technical Information

*Valid valve and rough-in position before installation

Toilet type.....One-piece
 Bowl shape.....Elongated
 Waste outlet.....Floor
 Flush type.....Dual flush
 Water consumption.....1.1/1.6 GPF | 4/6 LPF
 MAP.....1000gr.
 Flush action.....Cyclone
 Trapway fully glazed.....Ø 2 1/8" | 54mm
 Water surface.....5.5" x 7.8" | 140 x 200mm
 Rough-in.....12" | 305mm
 Seat-mounting holes.....5 1/2" | 140mm
 Flush valve.....Ø 2 1/4" | 58mm
 Water tank.....Fully vitrified
 Soft-close seat.....Included
 Warranty.....3 years porcelain / 1 year parts
 All product dimensions are nominal

Information Technique

*Valider la position de la valve d'alimentation et la plomberie brute avant l'installation

Type de toilette.....Mono-pièce
 Forme de la cuve.....Allongée
 Type d'installation.....Plancher
 Type de chasseDouble chasse
 Consommation d'eau.....1.1/1.6 GPF | 4/6 LPF
 MAP.....1000gr.
 Fonction de chasse.....Cyclone
 Évacuation vitrifiée.....Ø 2 1/8" | 54mm
 Surface d'eau.....5.5" x 7.8" | 140 x 200mm
 Installation/plomberie brute.....12" | 305mm
 Trous standard du siège.....5 1/2" | 140mm
 Valve de chasse.....Ø 2 1/4" | 58mm
 Réservoir d'eau.....Vitrifié
 Siège à rabat graduel.....Inclus
 Garantie.....3 ans porcelaine / 1 an pièces
 Toutes les dimensions sont nominales

